

Tray Cable

Construction: Stranded soft annealed copper.

Insulation: Thermoplastic polyvinyl chloride (PVC).

Color Coding: black, red, yellow, green (ground).

Temperature: 75° C

Voltage: 600 Volts

Specifications

UL Standard 83

Application

Suitable for use as power and control cable in direct burial applications. Maximum conductor operating temperatures of -25° C to 75° C in circuits not exceeding 600 volts.



AWG	Number of Conductors	Part Numbers	Approx. Ship Wt./M'	Conductor Stranding	Conductor Colors (Inners)	Jacket Color	Insulation Thickness (Jacket)
14	3	143CTC (P)	72.4	19	Black, Red, Blue	Black	0.045"
12	3	123CTC (P)	114.0	19	Black, Red, Blue	Black	0.045"
10	3	103CTC (P)	165.0	19	Black, Red, Blue	Black	0.045"
8	3 w/bare grd.	083CTC (P)	320.1	19	Numbrd. 1,2,3	Black	0.060"
6	3 w/bare grd.	063CTC (P)	437.0	19	Numbrd. 1,2,4	Black	0.060"
4	3 w/bare grd.	043CTC (P)	675.0	19	Numbrd. 1,2,5	Black	0.080"
2	3 w/bare grd.	023CTC (P)	954.5	19	Numbrd. 1,2,6	Black	0.080"

Put-up Codes (P): 1=500' put-up or 2=1000' put-up