

UF Irrigation Wire

Conductor construction is soft drawn bare copper meeting the requirements of ASTM Specifications B-3, B-8 and B-787. Gauge sizes 14 thru 8 are solid conductors. Sizes 6 thru 4/0 are stranded conductors.

The insulation is a high quality polyvinylchloride (PVC) for systems applications of up to 600 volts and conductor temperatures up to 60° C.

Application: Suitable for use as power and control wire for irrigation systems.

Conductor: Soft drawn bare copper (ASTM Specs. B-3, B-8 and B-787), Solid (14 awg thru 8 awg)
Stranded (6 awg thru 4/0 awg)

Insulation: Polyvinylchloride (PVC) **Temperature:** 60° C **Voltage:** 600 volts

Conductor Size	Insulation Thickness
14 awg thru 10 awg	.060
8 awg thru 2 awg	.080
1/0 awg thru 4/0 awg	.095

RoHS
Compliant

Material must be able to pass the following tests without showing signs of degradation:

Cold Bend — The insulation shall not show any cracks when sample is bent around a 3X mandrel after being subjected to -25° C for four (4) hours.

Sunlight Resistance Test — Samples conditioned for 300 hours of carbon-arc or xenon-arc exposure.



Regency's Type UF cables are intended for use in accordance with Article 339 and other applicable parts of the National Electrical Code in wiring systems operating at a potential of 600 V or less.