

Tray Cable Type TC

Conductor construction is soft drawn bare copper meeting the requirements of ASTM Specifications B-3 and B-787. Gauge sizes 12 thru 2 are stranded copper conductors.

The insulation is a color coded polyvinylchloride (PVC) rated for continuous use at 90° C dry or wet and up to 600 volts. Each insulated conductor is sheathed with a nylon jacket that meets the requirements for THHN or THWN wire. May be used in wet or dry locations, sunlight resistant, and suitable for direct burial. The Tray Cable will have a polyvinylchloride (PVC) outer jacket.

Application: Suitable for use as power and control tray cable in direct burial applications.

Conductor: Soft drawn bare copper (ASTM Specs. B-3 and B-787),
Stranded (12 awg thru 2 awg)

Insulation: Polyvinylchloride (PVC) with a nylon jacket **Outer Jacket:** Polyvinylchloride (PVC)

Temperature: 90° C dry or wet **Voltage:** 600 volts

Gauge Size	Number of Conductors	Conductor Stranding	Conductor Colors	Jacket Color
12	3	19	Black, Red, Blue	Black
10	3	19	Black, Red, Blue	Black
8	3 w/bare grd.	19	1-2-3	Black
6	3 w/bare grd.	19	1-2-3	Black
4	3 w/bare grd.	19	1-2-3	Black
2	3 w/bare grd.	19	1-2-3	Black

Call Regency Wire and Cable for availability of other sizes and number of conductor tray cables.

