



830 South West Street, Sikeston MO 63801

800-876-3020 / 573-472-2990 / FAX 573-471-3134



Paralleled Communication & Decoder Cable

Description:

Regency's Maxi Cable is manufactured for the control of Rain Bird's Maxi control systems. It is direct burial rated.

Conductor construction is tin coated, soft drawn bare copper meeting the requirements of ASTM Specification 33.

The two conductors shall be insulated with a high quality Polyvinylchloride (PVC) for system applications up to 600 volts. One conductor will be insulated black and the other conductor insulated red. Both conductors shall be of the same size as specified and/or shown on the drawings and as required for the proper operation of the Satellite and Decoder units connected to it.

The two conductors shall be laid parallel and pressure extruded with a solid color, low density, sunlight resistant polyethylene (PE) outer jacket. The standard colors for the jacket shall be white, red, green, blue, yellow and black.

Maxi Cable is constructed in accordance with Underwriters Laboratories, Inc.

Application:

Suitable for use as Rain Bird's communication wire for control of Maxi control systems.

Construction:

Conductor: Tin coated, soft drawn bare copper (ASTM Spec. 33).
Two (2) conductors
Solid (14 awg and 12 awg)

Insulation: Polyvinylchloride (PVC)

Outer Jacket: Polyethylene (PE)

Temperature: 60 C

Voltage: 600 volts

Gauge Size	Conductor Insulation	Outer Jacket
14	.060	.045
12	.060	.045