

PRODUCT RECAP

BARE COPPER WIRE

Soft Drawn Bare Copper, Suitable for Grounding Purposes

Size (AWG)	Stranding	Wt./1000'	Std. Pkg.
14	Solid	12.4	2x2000', 4x500', 2x1000'
12	Solid	19.8	2x1250', 4x500', 2x1000'
10	Solid	31.5	2x800', 4x500', 1x1000'
8	Solid	50	4x500', 1x1000'
6	Solid	79.5	4x315', 1x500', 1x1000'
4	Solid	126.3	4x200', 1x500', 1x1000'
2	Solid	200.9	2x125', 1x500', 1x1000'
8	7 Str.	51	4x500', 1x1000'
6	7 Str.	81	4x315', 1x500', 1x1000'
4	7 Str.	128.9	4x200', 1x500', 1x1000'
2	7 Str.	204.9	2x125', 1x500', 1x1000'

HUNTER® TWISTED DECODER CABLE

Soft Drawn Bare Copper, PE, 600V Rating

Size (AWG)	Stranding	Wt./1000'	Std. Pkg.
14	Solid	43.4	1x500', 1x1000', 1x2500'
12	Solid	61.6	1x500', 1x1000', 1x2500'

Put-Up Code (P): 1-500', 2-1000', 5-2500'

PARALLEL COMMUNICATION CABLE

Soft Drawn Bare Copper, PVC, 600V Rating

Size (AWG)	Stranding	Wt./1000'	Std. Pkg.
14	Solid	80	1x500', 1x1000', 1x2500'
12	Solid	103	1x500', 1x1000', 1x2500'

Put-Up Code (P): 1-500', 2-1000', 5-2500'

COMMUNICATION CABLES

Soft Drawn Bare Copper

Part No.	Size (AWG)	No. of Pairs	Wt./1000'	Std. Pkg.
PE-39	19	6	167	1x500', 1x1000'
PE-89	22	6	78	1x500', 1x1000'
PE-54	19	3	84	1x500', 1x1000'
DBS203P	20	3	59.7	1x500', 1x1000'
1804S	18	2	65	1x500', 1x1000'

Put-Up Code (P): 1-500', 2-1000'

TRAY CABLE, TYPE TC-DIRECT BURIAL

PVC Insulation with THHN/THWN Inners, 600V Rating

Part No.	Desc.	Wt./1000'	Std. Pkg.
123CTC(P)	12 Str/3 Cond.	141	1x500', 1x1000'
103CTC(P)	10 Str/3 Cond.	209	1x500', 1x1000'
083CTC(P)	8 Str/3 Cond. w/grd	323	1x500', 1x1000'
063CTC(P)	6 Str/3 Cond. w/grd	536	1x500', 1x1000'
043CTC(P)	4 Str/3 Cond. w/grd	701	1x500', 1x1000'
023CTC(P)	2 Str/3 Cond. w/grd	1020	1x500', 1x1000'

Put-Up Code (P): 1-500', 2-1000'

HUNTER® TWISTED DECODER CABLE JACKETED

Soft Drawn Bare Copper, PE, 600V Rating

Size (AWG)	Stranding	Wt./1000'	Std. Pkg.
14	Solid	55.6	1x500', 1x1000', 1x2500'
12	Solid	75	1x500', 1x1000', 1x2500'

Put-Up Code (P): 1-500', 2-1000', 5-2500'

TORO® DECODER CABLE

Soft Drawn Bare Copper, PE, 600V Rating

Size (AWG)	Stranding	Wt./1000'	Std. Pkg.
14	Solid	76	1x500', 1x1000', 1x2500'

Put-Up Code (P): 1-500', 2-1000', 5-2500'

TORO® COMMUNICATION CABLE

Soft Drawn Bare Copper, PVC, 600V Rating

Size (AWG)	Stranding	Wt./1000'	Std. Pkg.
16	7 Strand	54	1x500', 1x1000', 1x2500'

Put-Up Code (P): 1-500', 2-1000', 5-2500'

PRODUCT RECAP

UNDERGROUND LOW ENERGY CIRCUIT CABLE

PVC Insulation, 30V Rating

Part No.	Desc.	Wt./1000'	Std. Pkg.	Colors
18UF(C) (P)	18 Solid	13	4x500', 1x2500'	1-12
16UF(C)(P)	16 Solid	17	4x500', 2x1000', 1x2500'	1-12

Put-Up Code (P): 1-500', 2-1000', 5-2500'

UF IRRIGATION CABLE

PVC Insulation, 600V Rating, Underground Feeder Cable

Part No.	Desc.	Wt./1000'	Std. Pkg.	Colors
14UF(C)(P)	14 Solid	28	2x500', 1x2500'	1-12
12UF(C)(P)	12 Solid	37	2x500', 1x2500'	1-12
10UF(C)(P)	10 Solid	51	2x500', 1x1000', 1x2500'	1-9, 11
08UF(C)(P)	8 Solid	76	2x500', 1x1000', 1x2500'	1-8
06UF(C)(P)	6 Str	120	2x500', 1x1000', 1x2500'	1-5
04UF(C)(P)	4 Str	175	2x500', 1x1000', 1x2500'	1, 2, 3, 5
02UF(C)(P)	2 Str	280	2x500', 1x1000', 1x2500'	1, 2, 3, 5

Put-Up Code (P): 1-500', 2-1000'

FLAT JACKETED-TYPE UF-B W/ GROUND-DIRECT BURIAL

PVC Insulation with THHN/THWN Inners, 600V Rating

Part No.	Desc.	Wt./1000'	Std. Pkg.
142CWGJK(P)/143CWGJK(P)	14 Solid 2/3 w/grd.	53/93	1X500', 1X1000'
122CWGJK(P)/123CWGJK(P)	12 Solid 2/3 w/grd.	75/134	1X500', 1X1000'
102CWGJK(P)/103CWGJK(P)	10 Solid 2/3 w/grd.	140/194	1X500', 1X1000'
082CWGJK(P)/083CWGJK(P)	8 Str 2/3 w/grd.	213/330	1X500', 1X1000'
062CWGJK(P)/063CWGJK(P)	6 Str 2/3 w/grd.	305/449	1X500', 1X1000'

Put-Up Code (P): 0-250', 1-250', 1-500', 2-1000', 5-2500'

MULTI-CONDUCTOR IRRIGATION CONTROL CABLE

PE Jacket with PVC Inner Insulation with Rip Cord, 600V Rating

Part No.	Desc.	Wt./1000'	Std. Pkg.
18/02(P)	18 Solid/2 Cond.	20	2x250', 2x500', 1x1000', 1x2500'
18/03(P)	18 Solid/3 Cond.	27	2x250', 2x500', 1x1000', 1x2500'
18/04(P)	18 Solid/4 Cond.	34	2x250', 2x500', 1x1000', 1x2500'
18/05(P)	18 Solid/5 Cond.	43	2x250', 2x500', 1x1000', 1x2500'
18/06(P)	18 Solid/6 Cond.	49	2x250', 2x500', 1x1000', 1x2500'
18/07(P)	18 Solid/7 Cond.	57	2x250', 2x500', 1x1000', 1x2500'
18/08(P)	18 Solid/8 Cond.	64	2x250', 2x500', 1x1000', 1x2500'
18/09(P)	18 Solid/9 Cond.	71	2x250', 2x500', 1x1000', 1x2500'
18/10(P)	18 Solid/10 Cond.	79	2x250', 2x500', 1x1000', 1x2500'
18/12(P)	18 Solid/12 Cond.	93	2x250', 2x500', 1x1000', 1x2500'
18/13(P)	18 Solid/13 Cond.	100	1x250', 1x500', 1x1000', 1x2500'
18/16(P)	18 Solid/16 Cond.	123	1x250', 1x500', 1x1000'
18/19(P)	18 Solid/19 Cond.	144	1x250', 1x500', 1x1000'
18/25(P)	18 Solid/25 Cond.	185	1x250', 1x500', 1x1000'

Put-Up Code (P): 0-250', 1-250', 1-500', 2-1000', 5-2500'

PE SPRINKLER SYSTEMS CABLE

Polyethylene Insulation, 600V Rating, Direct Burial

Part No.	Desc.	Wt./1000'	Std. Pkg.	Colors
14PE(C)(P)	14 Solid	20	2x500', 1x2500'	1-12
12PE(C)(P)	12 Solid	27	2x500', 1x2500'	1-9, 11
10PE(C)(P)	10 Solid	40	2x500', 1x2500'	1-2, 5, 6

Put-Up Code (P): 1-500', 2-1000', 5-2500'

LOW VOLTAGE LIGHTNING CABLE

PVC Insulation, Flexible, Stranded Low Energy lightning Cable, 30V Rating

Part No.	Desc.	Wt./1000'	Std. Pkg.
18LC1(P)	18 Str/2 Cond.	27	4x250', 2x500'
16LC1(P)	16 Str/2 Cond.	33	2x250', 2x500', 1x1000'
14LC1(P)	14 Str/2 Cond.	47	2x250', 2x500', 1x1000'
12LC1(P)	12 Str/2 Cond.	69	2x250', 1x500', 1x1000'
10LC1(P)	10 Str/2 Cond.	95	1x250', 1x500'
08LC1(P)	8 Str/2 Cond.	155	1x250', 1x500'

Put-Up Code (P): 0-250', 1-500', 2-1000'



1500 West Malone / Sikeston, MO 63801
800.876.3020 / F: 800.333.5676